



DRIVEN BY POSSIBILITY™

HEAVY-DUTY PRODUCT RANGE – DRIVEALIGN® HD IDLER PULLEYS

PART NO.	NO. OF GROOVES	OUTSIDE DIAMETER	WIDTH (mm)	BEARING BORE INSIDE DIAMETER 1	BEARING BORE INSIDE DIAMETER 2	MATERIAL	CONTACT SURFACE	NOTES
36091	0	74	39.25	17	-	Steel	Smooth / backside	
36092	0	74	46.25	17	-	Steel	Smooth / backside	
36093	8	74	37	17	-	Steel	V ribbed grooved	
36095	0	74	33	17	-	Steel	Smooth / backside	
36096	0	86.5	39.4	17	-	Steel	Smooth / backside	
36135	0	95	32	10	-	Thermoplastic	Smooth / backside	
36157	6	87	31	17	-	Steel	V ribbed grooved	
36164	0	75	42.55	17	-	Steel	Smooth / backside	
36165	0	74	57	17	-	Steel	Smooth / backside	
36167	6	112	27.5	17	-	Steel	V ribbed grooved	
36170	8	101	30	12	-	Thermoplastic	V ribbed grooved	
36177	6	85	29	12	-	Steel	V ribbed grooved	
36187	0	90	32	M10	-	Steel	Smooth / backside	M10 Bolt



DRIVEN BY POSSIBILITY™

PART NO.	NO. OF GROOVES	OUTSIDE DIAMETER	WIDTH (mm)	BEARING BORE INSIDE DIAMETER 1	BEARING BORE INSIDE DIAMETER 2	MATERIAL	CONTACT SURFACE	NOTES
36195	0	74	47	M12	-	Steel	Smooth / backside	M12 Bolt
36196	0	32	32	M10	-	Steel	Smooth / backside	M10 Bolt
36223	6	83.5	29.5	17	-	Steel	V ribbed grooved	
36225	0	76	31.3	17	-	Steel	Smooth / backside	
36230	6	78	30	17	-	Steel	V ribbed grooved	
36231	8	75	36.5	17	-	Steel	V ribbed grooved	
36234	0	90	39.5	17	-	Steel	Smooth / backside	
36237	0	90	25	10	-	Steel	Smooth / backside	
36238	0	90	25	10.2	-	Steel	Smooth / backside	
36239	6	70	23	17	-	Steel	V ribbed grooved	
36259	0	80	48	10	-	Thermoplastic	Smooth / backside	
36269	0	74	42.7	17	-	Steel	Smooth / backside	
36282	12	74	54.63	17	-	Steel	V ribbed grooved	
36283	0	86	39	17	-	Steel	Smooth / backside	
36285	0	74	38.5	20	-	Steel	Smooth / backside	



DRIVEN BY POSSIBILITY™

PART NO.	NO. OF GROOVES	OUTSIDE DIAMETER	WIDTH (mm)	BEARING BORE INSIDE DIAMETER 1	BEARING BORE INSIDE DIAMETER 2	MATERIAL	CONTACT SURFACE	NOTES
36286	0	70	50	20	-	Steel	Smooth / backside	
36287	0	110	39.5	17	-	Steel	Smooth / backside	
36288	8	107	39.5	17	-	Steel	V ribbed grooved	
36291	0	75	33	12	-	Steel	Smooth / backside	
36304	6	70	26	8	-	Thermoplastic	V ribbed grooved	
36308	8	82.6	36	30	-	Steel	V ribbed grooved	
36341	8	74	36	17	-	Steel	V ribbed grooved	
36500	0	95	40	10	-	Thermoplastic	Smooth / backside	
36501	0	74	35.5	10	-	Steel	Smooth / backside	
36508	9	81	36.5	18	-	Thermoplastic	Smooth / backside	
36514	0	74	34	17.5	-	Steel	Smooth / backside	
36515	0	107	34	M12	-	Steel	Smooth / backside	M12 Bolt
36516	0	65	32	M10	-	Steel	Smooth / backside	M10 Bolt
36517	8	81	34	11	-	Thermoplastic	V ribbed grooved	
36518	0	74	32	11	-	Thermoplastic	V ribbed grooved	



DRIVEN BY POSSIBILITY™

PART NO.	NO. OF GROOVES	OUTSIDE DIAMETER	WIDTH (mm)	BEARING BORE INSIDE DIAMETER 1	BEARING BORE INSIDE DIAMETER 2	MATERIAL	CONTACT SURFACE	NOTES
36519	10	73	38.5	N.A	N.A	Steel	V ribbed grooved	With Casting Arm
36528	0	78	38	M10	-	Steel	Smooth / backside	M10 Bolt
36529	0	78	38	M10	-	Steel	Smooth / backside	M10 Bolt
36623	0	78	38	M10	-	Steel	Smooth / backside	M10 Bolt
36624	10	73	39.5	17	-	Steel	V ribbed grooved	
36742	0	70	34	M10	-	Steel	Smooth / backside	M10 Bolt
38076	0	75	40	30	-	Steel	Smooth / backside	
38089	0	80	25.5	8	-	Steel	Smooth / backside	
38092	6	70	26.5	8	14.5	Thermoplastic	V ribbed grooved	
38709	0	65	36	12	-	Steel	Smooth / backside	