



DRIVEN BY POSSIBILITY™

CLEAN MASTER™ HOSE WATER BLAST



ULTRA HIGH PRESSURE FOR INTENSE APPLICATIONS.

GATES Clean Master™ Water Blast hoses are designed for ultra high pressure cold water cutting devices, blasting applications and also cleaning equipment, including high pressure water streams to remove growth on marine vessels.

We believe operating challenges are made to be overcome. That's why thousands of industrial facilities, global operations, and OE manufacturers around the world choose Gates hose and hydraulic systems to power their most demanding fluid power applications.



FEATURES + BENEFITS

Ultra high working pressure of 1,034 Bar (15,000 PSI) for extreme applications

Clean Master™ Water Blast hose is designed for sea water or fresh water

XtraTuff™ cover offers 25X better abrasion resistance than a standard rubber cover, along with improved resistance to oil, ozone and UV-rays for a longer lasting hose

Alternating layers of of spiral, high-tensile wire reinforcement offer added strength and flexibility

Exclusively compatible with GATES 2-piece Water Blast (WTB) couplings for maximum safety and performance

CLEAN MASTER™ WATER BLAST HOSE LINE PRODUCT SPECIFICATIONS

CONSTRUCTION	NBR Nitrile Reinforcement Tube. Four alternating layers of spiral high-tensile wire reinforcement (sizes -6 and -8). Six alternating layers of spiral high-tensile wire reinforcement on size -12.
COVER	Black (all types). All non-marking and abrasion resistant with XtraTuff™ cover. Meets MSHA flame resistance.
WORKING PRESSURE	Working pressure of 1,034 Bar (15,000 PSI) for all sizes.
TEMPERATURE RANGE	-4°F to +158°F (-20°C to +70°C) continuous service.

APPLICATIONS

Marine Cleaning
Paint Removal
Hydro-Demolition of Concrete
Tank Cleaning

**OUR GLOBAL
FOOTPRINT
HELPS YOU
MOVE FORWARD.**

HOSE SIZE	SPIRAL LAYERS	ID (INCH)	ID (MM)	OD (INCH)	OD (MM)	WP (PSI)	WP (BAR)	BURST (PSI)	BURST (Bar)	MBR (INCH)	MBR (MM)	WEIGHT (LBS/FT)	WEIGHT (KG/100M)	COLOR
-6	4	3/8	9.5	0.84	21.2	15,000	1,034	37,500	2,590	9.0	229	0.59	88	Black
-8	4	1/2	12.5	0.97	24.6	15,000	1,034	37,500	2,590	9.0	229	0.95	141	Black
-12	6	3/4	19.0	1.36	34.5	15,000	1,034	37,500	2,590	9.0	229	1.53	228	Black

GATES AUSTRALIA PTY LTD

1-15 Hydrive Close, Dandenong South, Victoria, 3175
PH: +61 3 9797 9666 FAX: +61 3 9797 9600

GATESAUSTRALIA.COM.AU

FOLLOW: GATES AUSTRALIA

