

COOLING SYSTEM



GREEN STRIPE® VIBRAFLEX® COOLANT HOSE



For heavy-duty applications requiring short length hose that must absorb vibration and/or fitting misalignment. High flexibility reduces installation time and provides lower cost per kilometre operation.

- Oil and heat resistant nitrile tube.
- Oil, abrasion and heat resistant neoprene cover.

- Exceeds SAE J20 (Class B Tube and Class C Cover).
- Two-ply fabric reinforced.

Temperature Rating: -40° to +100°C

CAUTION: Do not use for gasoline or diesel transfer applications.

PART NO.	I.D.	LENGTH	WORK PRESS [PSI]
23505	1 1/4" [38mm]	4" [100mm]	70
23511	1 3/8" [35mm]	5" [125mm]	60
23515	1 1/2" [38mm]	5" [125mm]	60
23520	1 3/4" [44mm]	5" [125mm]	55
23531	2" [50mm]	3 1/2" [89mm]	50
23533	2" [50mm]	5" [125mm]	50
23547	2 1/4" [57mm]	4 1/2" [115mm]	40
23557	2 3/8" [60mm]	5" [125mm]	35
23559	2 3/8" [60mm]	6 1/4" [158mm]	35

PART NO.	I.D.	LENGTH	WORK PRESS [PSI]
23562	2 1/2" [64mm]	4 1/2" [115mm]	35
23550	2 1/2" [64mm]	6" [150mm]	35
23566	2 3/4" [70mm]	3 1/4" [82mm]	30
23567	1 3/4" [70mm]	4 1/2" [115mm]	30
23568	2 3/4" [70mm]	5 3/8" [136mm]	30
23572	3" [76mm]	4" [100mm]	25
23575	3" [76mm]	7" [178mm]	25
23585	3 1/2" [89mm]	5 1/2" [140mm]	25