



DRIVEN BY POSSIBILITY™

THE LATEST IN INDUSTRIAL RUBBER SYNCHRONOUS TECHNOLOGY:

POWERGRIP™ GT4™

8MGT AND 14MGT

INTRODUCING A NEWLY DESIGNED ETHYLENE ELASTOMER HIGH-TORQUE SYNCHRONOUS BELT.

Engineered with the latest in advanced technology and materials science expertise, Gates® PowerGrip™ GT4™ delivers the highest power-carrying capacity of any belt in its class. Utilising all new advanced materials, Gates designed a belt with increased chemical resistance and larger temperature range capability.

The NEW GT4™ belt delivers improved performance over a wide range of industrial applications. The 8MGT and 14MGT pitches are the optimum choice for high performance drives in the machine tool, paper and textile industries where durability and low maintenance are required.

From resource processing to heavy manufacturing, automated production to custom assembly — Gates solutions improve uptime, efficiency, productivity, reliability and safety for industries around the world.

FEATURES + BENEFITS

The most advanced combination of materials and technology enable:

- Higher power-carrying capacity giving you the option to use a narrow belt
- No lubrication and no retensioning eliminates maintenance costs throughout the life of the belt
- Larger temperature range capability
- Improves Ergonomics — less weight reduces fatigue and strain during installation
- Environmentally Friendly — made without harmful chlorinated compounds

POWERGRIP™ GT4™ BELTS:

THE LATEST IN SYNCHRONOUS BELT TECHNOLOGY

Discover the superior performance, uptime, reliability and total cost of ownership with Gates® PowerGrip™ GT4™ belts for factories, plants and other industrial equipment. Combining advanced materials science and process engineering, Gates introduces a new belt-driven solution for narrower drives utilising all new materials offering larger temperature range capability, improved chemical resistance and higher power capacity.

INDUSTRIES + END MARKETS
Construction + Mining
Forestry + Agriculture
Textile + Laundry
Stationary Machinery + Tools
Pulp + Paper
Food Processing
Packaging + Automation

APPLICATIONS
Heavy-Duty Equipment
Fans + Pumps
Conveyor Systems
Industrial Machines
Compressors
Centrifuges
Horizontal + Vertical Positioning

SECTIONS + DIMENSIONS				
Section	Pitch (mm)	Tooth Height (mm)	Belt Height (mm)	Length Range (mm)
8 MGT	8.0	3.4	5.6	384 - 4400
14 MGT	14.0	6.0	10.0	966 - 6860



SAFER, STRONGER BELT-DRIVE SOLUTIONS

WHY POWERGRIP™ GT4™?

- Larger Temperature Range
- Higher Power Capacity for Optimum Performance
- Improved Chemical Resistance
- Increased Uptime
- Improved Safety
- Improved Ergonomics
- Rust Free + Safe for Use in Food Handling Spaces
- Reduced Environmental Risk
- No Lubrication + No Stretching
- High Tooth Jump Resistance

PRODUCT SPECIFICATIONS

- Standard widths of 20,30, 50, 85 mm (8MGT); 40, 55, 85, 115, 170 mm(14MGT)
- Fully operational in a wide range of temperatures: 40°C to +140°C (-40°F to +284°F) *For intermittent use
- Static conductive (ISO9563) and for conditions described in the Directive 2014/34/ EU-ATEX

CONTACT YOUR LOCAL GATES REPRESENTATIVE OR GATES CUSTOMER SERVICE AT +61 3 9797 9688 TO LEARN MORE.

GATES AUSTRALIA PTY LTD

1-15 Hydrive Close, Dandenong South, Victoria, 3175
PH: +61 3 9797 9666 FAX: +61 3 9797 9600

GATESAUSTRALIA.COM.AU

FOLLOW US: GATESAUSTRALIA



496-3035 09/2020