



IDEAL™ PART STAINLESS STEEL NON-PERFORATED CLAMPS

These clamps are specially designed for use with soft silicone and rubber hose applications making them ideally suited for radiator hose applications.

Part stainless steel (W2) construction provides an excellent level of corrosion resistance that suits under bonnet applications at an affordable price.

This range comes in both 9mm and 12mm band widths to help provide a solution for all applications.



9mm Part Stainless Non-Perforated Clamps

Band: 9mm, 430 Grade Stainless Steel

Housing: 430 Grade Stainless Steel

Screw: 7mm Plated Carbon Steel

Ideal™ Part No.	Clamping Range				Recommended Torque	
	Metric (mm)		English (in.)		Installation (in-lb/NM)	Ultimate (in-lb/NM)
	Min. Dia.	Max. Dia.	Min. Dia.	Max. Dia.		
53916	8	16	5/16"	5/8"	18/2.0	35/4.0
53920	12	20	15/32"	25/32"	18/2.0	35/4.0
53922	12	22	15/32"	7/8"	26/3.0	40/4.5
53925	16	25	5/8"	1"	26/3.0	40/4.5
53927	16	27	5/8"	1 - 1/16"	26/3.0	40/4.5
53932	20	32	25/32"	1 - 1/4"	26/3.0	40/4.5
53935	23	35	7/8"	1 - 3/8"	26/3.0	40/4.5
53940	25	40	1"	1 - 9/16"	26/3.0	40/4.5
53945	30	45	1 - 3/16"	1 - 3/4"	26/3.0	40/4.5
53950	30	50	1 - 3/16"	1 - 31/32"	26/3.0	40/4.5
53955	35	55	1 - 3/8"	2 - 3/16"	26/3.0	40/4.5
53965	45	65	1 - 3/4"	2 - 1/2"	26/3.0	40/4.5
53970	50	70	1 - 31/32"	2 - 3/4"	26/3.0	40/4.5
53975	55	75	2 - 3/16"	2 - 15/16"	26/3.0	40/4.5
53980	60	80	2 - 3/8"	3 - 1/8"	26/3.0	40/4.5
53990	70	90	2 - 3/4"	3 1/2"	26/3.0	40/4.5
53995	75	95	3"	3 - 3/4"	26/3.0	40/4.5
539100	80	100	3 1/8"	3 15/16"	26/3.0	40/4.5
539110	90	110	3 1/2"	4 - 5/16"	26/3.0	40/4.5
539120	100	120	3 15/16"	4 - 23/32"	26/3.0	40/4.5

All parts sold in box quantities of 10.

NB: Parts shaded in grey above are non stocked lines at Gates. Please contact customer service on (03) 9797 9688 for further information



IDEAL™ PART STAINLESS STEEL NON-PERFORATED CLAMPS



12mm Part Stainless Non-Perforated Clamps

Band: 12mm, 430 Grade Stainless Steel

Housing: 430 Grade Stainless Steel

Screw: 7mm Plated Carbon Steel

Ideal™ Part No.	Clamping Range				Recommended Torque	
	Metric (mm)		English (in.)		Installation (in-lb/NM)	Ultimate (in-lb/NM)
	Min. Dia.	Max. Dia.	Min. Dia.	Max. Dia.		
531225	16	25	5/8"	1"	44/5.0	71/8.0
531227	16	27	5/8"	1 - 1/16"	44/5.0	71/8.0
531232	20	32	25/32"	1 - 1/4"	44/5.0	73/8.3
531235	23	35	7/8"	1 - 3/8"	44/5.0	73/8.3
531240	25	40	1"	1 - 9/16"	44/5.0	73/8.3
531245	30	45	1 - 3/16"	1 - 3/4"	44/5.0	73/8.3
531250	30	50	1 - 3/16"	1 - 31/32"	44/5.0	73/8.3
531260	40	60	1 - 9/16"	2 - 3/8"	44/5.0	73/8.3
531265	45	65	1 - 3/4"	2 - 1/2"	44/5.0	73/8.3
531270	50	70	1 - 31/32"	2 - 3/4"	44/5.0	73/8.3
531275	55	75	2 - 3/16"	2 - 15/16"	44/5.0	73/8.3
531280	60	80	2 - 3/8"	3 - 1/8"	44/5.0	73/8.3
531290	70	90	2 - 3/4"	3 1/2"	44/5.0	73/8.3
5312100	80	100	3 1/8"	3 15/16"	44/5.0	73/8.3
5312110	90	110	3 1/2"	4 - 5/16"	44/5.0	73/8.3
5312120	100	120	3 15/16"	4 - 23/32"	44/5.0	73/8.3
5312130	110	130	4 - 5/16"	5 - 1/8"	44/5.0	73/8.3
5312140	120	140	4 - 23/32"	5 - 1/2"	44/5.0	73/8.3
5312150	130	150	5 - 1/8"	5 - 29/32"	44/5.0	73/8.3
5312160	140	160	5 - 1/2"	6 - 5/16"	44/5.0	73/8.3

All parts sold in box quantities of 10.

NB: Parts shaded in grey above are non stocked lines at Gates. Please contact customer service on (03) 9797 9688 for further information



DISTRIBUTED BY:
Gates Australia Pty Ltd
1-15 Hydrive Close, Dandenong South, VIC 3175

PH: +61 3 9797 9666
FAX: +61 3 9797 9600

www.GatesAustralia.com.au